



The DUBEX MODEL 8

The top model in 3-point hitched spraying machines from Dubex is the Model 8. A compact machine with an empty weight of 810 kg and a tank capacity of max 1100 l Standard equipped with the super-balance boom suspension and solid spraying booms which are compactly folded alongside the machine. A professional machine perfectly suited for bigger areas

Typical Dubex reliability

To efficient work on bigger areas the Model 8 is equipped with 15, 18, 21 or 24 meter spraying booms. These are hydraulically operated and foldable alongside the machine. Standard equipped with the super balance system, hydraulic balance correction, automatic fold-back and yaw control. Useful options which, because of the big working width, considerable endure the lifetime of the Model 8.



Compact stability

The Model 8 - like all other Dubex sprayers - has the disposal of a light and strong polyethylene tank. Exceptional easy in use: because of the smooth inside and standard tank cleaner, tank cleaning is very easy. The main tank is, together with the clean water tank, compactly fitted into a solid frame. An extreme stable unit.



Performance to count on

Model 8 offers you a manual operated valve block with 5 or 7 sections and a robust piston membrane pump of 210 l/min. Bigger capacities, up to 300 l/min, are available. Also electro hydraulic operation of the spraying booms and individual operation of the outer sections come as an option. The model 8 combines the performance of a trailed sprayer with a 3-point hitch frame.



Empty weight: 900 kg
Length: 3,68 m
Width: 2,82 m
Height: 2,65 m

Tank nominal volume:
700, 900 or 1100 liter
Tank actual volume:
770, 990 or 1190 liter

Working width:
15, 18, 21 or 24 meter

Dubex BV
Ohmweg 10, NL-9503 GW Stadskanaal
+31599 696000 www.dubex.com, info@dubex.com





| Dubex 3-point hitch sprayers | Model |
|---|---------------------|
| | 8 |
| Tank 700 l (=770 l) | X |
| Tank 900 l (=990 l) | 0 |
| Tank 1100 l (=1190 l) | 0 |
| Working width: | |
| 15 m | 0 |
| 18 m | 0 |
| 21 m | 0 |
| 24 m | 0 |
| 27 m | 0 |
| Clean water tank 80 l | X |
| Hydraulic operated booms | X |
| Automatic fold-back | X |
| Yaw control | X |
| Hydraulic boom lift | X |
| Super balance boom suspension | X |
| Hydraulic balance correction | X |
| Electrical balance correction | 0 |
| Outer sections left and right individual | 0 |
| Hydraulic valve block | 0 |
| Electro-hydraulic operation | 0 |
| Manual operated pressure unit | X |
| Manometer analogue | X |
| Electr. Pressure unit with section valves | 0 |
| Manometer digital | 0 |
| Number of sections | 5 or 7 ¹ |
| In-line pressure filter 100 mesh | X |
| Computer SprayDos | 0 |
| Stainless steel spray-line | X |
| Single nozzle bodies | 0 |
| Quadruple nozzle bodies | 0 |
| Spraying gun + 5 meter hose | X |
| Pump 210 l/min | X |
| Pump 260 l/min | 0 |
| Pump 300 l/min | 0 |
| PTO | X |
| Suction hose 6 meter incl. float & strainer | X |
| Tank level indicator | X |
| Tank cleaner in the tank | 1 |
| Can cleaning system | X |
| Drain valve | X |
| Road lighting and reflectors | X |
| | |
| | |
| | |
| x= standard o= option | |



DUBEX B.V.
 Ohmweg 10, NL-9503 GW Stadskanaal
 Rufnr. +31 599 696000, Fax +31 599 696009
 www.dubex.com, info@dubex.com

Strong at crop protection